

AR66

AR66 is suitable for residential and small commercial and industrial scenarios, with up to 50 units in parallel and an energy range from 5.12 kWh to 256 kWh. High cycle times and security ensure users' electricity freedom and safety.



Flexible Expansion

Up to 50 units in parallel,
5.12kWh--256kWh capacity



1C Discharge

Simultaneously supplying power to
multiple loads, no need to worry
about power outages



Automatic Self-heating

-20°C to 55°C operating tem-
perature (optional)



Ultra Safe

Intelligent fire extinguishing
system, detects and extin-
guishes a fire in 5s(optional)



Easy Installation

Support wall-mounted,
floor-mounted installations,
high space utilization



Smart Management

Real-time system monitoring,
remote control, OTA updates

Model	AR66
Battery Type	LiFePO ₄
Nominal Battery Energy	5.12kWh
Nominal Capacity	100Ah
Nominal Voltage	51.2V
Operating Voltage	44.8–57.6V
Recommended Charge & Discharge C Rate	0.5C
Maximum Discharge C Rate	1C
Recommended Charge/Discharge Current	50A
Max. Charge/Discharge Current	Charge 75A Discharge 100A
Peak Discharge Current	120A@10min
Depth of Discharge (DOD)	95%
Net Weight	65kg
Dimension(W/D/H)	488/515/150mm
Charging Temp. Range	0–55°C/–20–55°C (with heating function)
Discharging Temp. Range	–20–55°C
Communication	CAN/RS485
WIFI Module	Built-in WIFI module; APP OTA function
Cycle Life *	≥8000 Cycles
Protection Level	IP40
Active fire protection system	Optional Aerosol fire extinguisher
Expansion	Up to 50 units in parallel
Pros	Can be used in both off-grid and hybrid setups, compact design
Certification & Safety Standard	UN38.3/CE-EMC/IEC62619/CE-RED
Compatible Inverters	SMA/Schneider/Victron energy/Ingteam/Solis/GoodWe/ Growatt/Solplanet/Luxpower/DEYE etc.

* Test conditions: 0.2C Charging& Discharging, @25°C, 95% DOD, 70%EOL